VUTL003R075NA

Datasheet

VMDSEMI

7.5mΩ, 30V, N-Channel Power MOSFET VUTL003R075NA

General Description

$V_{(BR)DSS}$	$R_{DS(ON)_max}$	I_D
30V	7.5mΩ@10V	47A
	14mΩ@4.5V	

Symbol



Figure 1 Symbol of VUTL003R075NA

Features

- Trench Technology Power MOSFET
- Low Gate Charge
- Low Gate Resistance
- Low $R_{DS(ON)}$
- 100% UIS Tested

Package Type



TO-252-2L

Figure 2 Package Type of VUTL003R075NA

Application

- Power Switch
- DC/DC Converter

Ordering Information

Product Name	Package
VUTL003R075NA	TO-252-2L

Absolute Maximum Ratings (T_A= 25 ºC, unless otherwise specified)

Parameter		Symbol	Rating	Unit
Drain-Source Voltage		V_{DSS}	30	V
Gate-Source Voltage		V_{GSS}	±20	V
Continuous Drain Current Note1	T_C= 25 ºC	I_D	47	A
Pulsed Drain Current Note2		I_{DM}	188	
Avalanche Current Note3		I_{AS}	33	A
Single Pulsed Avalanche Energy Note3		E_{AS}	54.5	mJ
Total Power Dissipation Note5	T_C= 25 ºC	P_D	31.2	W
Total Power Dissipation Note6	T_A= 25 ºC		2.5	W
Junction Temperature		T_J	150	ºC
Storage Temperature		T_{STG}	-55 to 150	ºC

Thermal Resistance

Parameter	Symbol	Min	Typ	Max	Unit
Thermal Resistance, Junction-to-Ambient Note6	$R_{\theta JA}$		50		ºC/W
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$		4		ºC/W

Electrical Characteristics (T_A= 25 ºC, unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Statistic Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V, I_D= 250uA	30			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}= 24V, V_{GS}=0V			1	uA
Gate-Body Leakage Current	I_{GSS}	V_{GS} = ±20V, V_{DS}= 0V			±100	nA
Gate Threshold Voltage[Note4]	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=250uA	1.0	1.5	3.0	V
Static Drain-Source On-Resistance[Note4]	$R_{DS(ON)}$	V_{GS}=10V, I_D=20A		6.0	7.5	mΩ
		V_{GS}=4.5V, I_D= 20A		9.0	14	
Dynamic Characteristics						
Input Capacitance	C_{ISS}	V_{DS}=15V		990.2		pF
Output Capacitance	C_{OSS}	V_{GS}=0V		143.7		pF
Reverse Transfer Capacitance	C_{RSS}	f=1MHz		128.2		pF
Total Gate Charge	Q_g	V_{DS}=15V		22.2		nC
Gate-Source Charge	Q_{gs}	V_{GS}=4.5V		3.0		
Gate-Drain Charge	Q_{gd}	I_D= 20A		4.3		
Gate Resistance	Rg	f = 1MHz, Open drain		1.95		Ω
Switching Parameters						
Turn-on Delay Time	$t_{d(on)}$	V_{DD}= 15V		6.5		ns
Turn-on Rise Time	t_r	V_{GS}= 10V		2		
Turn-off Delay Time	$t_{d(off)}$	R_L=0.75Ω		17		
Turn-off Fall Time	t_f	R_G=3Ω		3.5		
Diode Characteristics						
Diode Forward Voltage [Note4]	V_{SD}	V_{GS}=0V, I_S= 10A			1.2	V

Notes :

1.The maximum current rating is limited by package.And device mounted on a large heatsink

2.Pulse Test : Pulse Width ≤ 10μs, duty cycle ≤ 1%.

3.E_{AS} condition: V_{DD} = 15V,V_{GS} = 10V, L = 0.5mH, R_G = 25Ω Starting T_J = 25°C.

4.Pulse Test : Pulse Width ≤ 300μs, duty cycle ≤ 2%.

5.The power dissipation P_D is limited by $T_{J(MAX)}$ = 150°C.And device mounted on a large heatsink

6.Device mounted on 1in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A =25°C.

Typical Performance Characteristics

Figure 3: Transfer Characteristics



Figure 4: Output Characteristics



Figure 5: On-Resistance vs. Drain Current



Figure 6: On-Resistance vs. Gate Voltage



Figure 7: Body Diode Characteristics



Figure 8: Threshold Voltage



Figure 9: Typical Capacitance



Figure 10: Safe Operating Area



Figure 11: Normalized Maximum Transient Thermal Impedance



Mechanical Dimensions:

TO-252-2L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
b	0.635	0.770	0.025	0.030
c	0.460	0.580	0.018	0.023
D	6.500	6.700	0.256	0.264
D1	5.100	5.460	0.201	0.215
D2	4.830 REF.		0.190 REF.	
E	6.000	6.200	0.236	0.244
e	2.186	2.386	0.086	0.094
L	9.712	10.312	0.382	0.406
L1	2.900 REF.		0.114 REF.	
L2	1.400	1.700	0.055	0.067
L3	1.600 REF.		0.063 REF.	
L4	0.600	1.000	0.024	0.039
Φ	1.100	1.300	0.043	0.051
θ	0°	8°	0°	8°
h	0.000	0.300	0.000	0.012
V	5.250 REF.		0.207 REF.	

NOTICE

Hangzhou VMD Semiconductor Co., Ltd (VMD) reserves the right to make changes without notice in order to improve reliability, function or design and to discontinue any product or service without notice. Customers should obtain the latest relevant information before orders and should verify that such information is current and complete. All products are sold subject to VMD's terms and conditions supplied at the time of order acknowledgement.

VMD, its affiliates, agents, and employees, and all persons acting on its or their behalf, disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.
VMD disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify VMD's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

VMD warrants performance of its hardware products to the specifications at the time of sale, testing, reliability and quality control are used to the extent VMD deems necessary to support this warrantee. Except where agreed upon by contractual agreement, testing of all parameters of each product is not necessarily performed.

VMD does not assume any liability arising from the use of any product or circuit designs described herein. Customers are responsible for their products and applications using VMD's components. To minimize risk, customers must provide adequate design and operating safeguards.

VMD does not warrant or convey any license to any intellectual property rights either expressed or implied under its patent rights, nor the rights of others. Reproduction of information in VMD's data sheets or data books is permissible only if reproduction is without modification or alteration. Reproduction of this information with any alteration is an unfair and deceptive business practice.

VMD is not responsible or liable for such altered documentation. Resale of VMD's products with statements different from or beyond the parameters stated by VMD for that product or service voids all express or implied warrantees for the associated VMD product or service and is an unfair and deceptive business practice.

All Rights Reserved.

Via-Media Semiconductor Limited Company

http://www.vmdsemi.com

Main Sites:

- **Headquarters**

Hangzhou Via-Media Semiconductor Co., LTD.
1305-1306, Building 71, No. 90, Wensan Road, Xihu District, Hangzhou, Zhejiang Province, P.R. China
Tel: +86-0571-8515 0563

- **Chengdu Office**

Chengdu Winhi Semiconductor Co., LTD.
Floor 15, Building 5, No. 171, Hele 2nd Street, Chengdu, Sichuan Province, P.R. China
Tel: +86-028-8505 0771

- **Shanghai**

Shanghai R&D Center.
1506~1508, Xinyin Building, 888 Yishan Road, Shanghai, P.R of China
Tel: +86- 021-54201999

- **Shenzhen**

Shenzhen Sales Center.
17B, No.1 Phoenix Building, 2008 Shennan Road, Shenzhen, P.R of China
Tel: +86-0755- 82570682

- **Xi'an**

Xi'an R&D Center
1703B, Building A, Greenland Center, Jinye Road, High-Tech Zone, Xi'an, Shaanxi, P.R of China