



VMDSEMI

**VUSB002R570PB**

**Datasheet**



VMDSEMI

## General Description

## Symbol

$V_{(BR)DSS}$	$R_{DS(ON)_{max}}$	$I_D$
-20V	57mΩ@-4.5V	-3.2A
	95mΩ@-2.5V	




Figure 1 Symbol of VUSB002R570PB


## Features

- Trench FET Power MOSFET
- Excellent  $R_{DS(on)}$  and Low Gate Charge

## Application

- DC/DC Converter
- Load Switch for Portable Devices
- Battery Switch

## Package Type



1. GATE
2. SOURCE
3. DRAIN

## SOT-23

Figure 2 Package Type of VUSB002R570PB

## Ordering Information

Product Name	Package
VUSB002R570PB	SOT-23

**Absolute Maximum Ratings** ( $T_A = 25\text{ °C}$ , unless otherwise specified)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	$V_{DSS}$	-20	V
Gate-Source Voltage	$V_{GSS}$	$\pm 8$	V
Continuous Drain Current <sup>Note1</sup>	$I_D$	-3.2	A
Pulsed Drain Current <sup>Note2</sup>	$I_{DM}$	-10	
Total Power Dissipation <sup>Note4</sup>	$P_D$	1.3	W
Junction Temperature	$T_J$	150	°C
Storage Temperature	$T_{STG}$	-55 to 150	°C

**Thermal Resistance**

Parameter	Symbol	Min	Typ	Max	Unit
Thermal Resistance, Junction-to-Ambient <sup>Note5</sup>	$R_{\theta JA}$		96		°C/W





**Electrical Characteristics** ( $T_A = 25\text{ }^\circ\text{C}$ , unless otherwise specified)


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
<b>Statistic Characteristics</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V, I_D=250\mu A$	-20			V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=-20V, V_{GS}=0V$			-100	nA
Gate-Body Leakage Current	$I_{GSS}$	$V_{GS}=\pm 8V, V_{DS}=0V$			$\pm 100$	nA
Gate Threshold Voltage <sup>Note3</sup>	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	-0.4	-0.7	-1	V
Static Drain-Source On-Resistance <sup>Note3</sup>	$R_{DS(on)}$	$V_{GS}=-4.5V, I_D=-2.5A$		44	57	mΩ
		$V_{GS}=-2.5V, I_D=-2.0A$		64	95	
Forward Transconductance <sup>Note3</sup>	$g_{FS}$	$V_{DS}=-5V, I_D=-5A$	3			S
<b>Dynamic Characteristics</b>						
Input Capacitance	$C_{ISS}$	$V_{DS}=-10V$		548		pF
Output Capacitance	$C_{OSS}$	$V_{GS}=0V$		96		pF
Reverse Transfer Capacitance	$C_{RSS}$	$f=1MHz$		89		pF
Total Gate Charge	$Q_g$	$V_{DS}=-6V$		10		nC
Gate-Source Charge	$Q_{gs}$	$V_{GS}=-4.5V$		1.7		
Gate-Drain Charge	$Q_{gd}$	$I_D=-5A$		2.6		
Gate Resistance	$R_g$	$f=1MHz, \text{Open drain}$		45	50	Ω
<b>Switching Parameters</b>						
Turn-on Delay Time	$t_{d(on)}$	$V_{DD}=-6V$		26	40	ns
Turn-on Rise Time	$t_r$	$V_{GS}=-4.5V$		24	40	
Turn-off Delay Time	$t_{d(off)}$	$R_L=6\Omega$		45	75	
Turn-off Fall Time	$t_f$	$R_G=1\Omega, I_D=-4A$		18	20	
<b>Diode Characteristics</b>						
Diode Forward Voltage <sup>Note3</sup>	$V_{SD}$	$V_{GS}=0V, I_S=-4A$		-0.8	-1.2	V
Continuous Source Current	$I_S$	$T_C=25\text{ }^\circ\text{C}$			-1.5	A
Pulsed Source Current	$I_{SM}$				-20	
Diode Reverse Recovery Time	$t_{rr}$	$I_F=-4A, dI/dt=100A/us$			40	ns
Diode Reverse Recovery Charge	$Q_{rr}$				30	nC

Notes :


- 1.The maximum current rating is limited by package.And device mounted on a large heatsink.
- 2.Pulse Test : Pulse Width  $\leq 10\mu s$ , duty cycle  $\leq 1\%$ .
- 3.Pulse Test : Pulse Width  $\leq 300\mu s$ , duty cycle  $\leq 2\%$ .
- 4.The power dissipation  $P_D$  is limited by  $T_{J(MAX)} = 150^\circ\text{C}$ .And device mounted on a large heatsink
- 5.Device mounted on  $1in^2$  FR-4 board with 2oz. Copper, in a still air environment with  $T_A = 25^\circ\text{C}$ .

## Typical Performance Characteristics





# VMDSEMI

**Mechanical Dimensions:**
**SOT-23 Package Information**


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0	0.100	0	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.150	1.500	0.045	0.059
E1	2.250	2.650	0.089	0.104
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

## NOTICE

Hangzhou VMD Semiconductor Co., Ltd (VMD) reserves the right to make changes without notice in order to improve reliability, function or design and to discontinue any product or service without notice. Customers should obtain the latest relevant information before orders and should verify that such information is current and complete. All products are sold subject to VMD's terms and conditions supplied at the time of order acknowledgement.

VMD, its affiliates, agents, and employees, and all persons acting on its or their behalf, disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

VMD disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify VMD's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

VMD warrants performance of its hardware products to the specifications at the time of sale, testing, reliability and quality control are used to the extent VMD deems necessary to support this warrantee. Except where agreed upon by contractual agreement, testing of all parameters of each product is not necessarily performed.

VMD does not assume any liability arising from the use of any product or circuit designs described herein. Customers are responsible for their products and applications using VMD's components. To minimize risk, customers must provide adequate design and operating safeguards.

VMD does not warrant or convey any license to any intellectual property rights either expressed or implied under its patent rights, nor the rights of others. Reproduction of information in VMD's data sheets or data books is permissible only if reproduction is without modification or alteration. Reproduction of this information with any alteration is an unfair and deceptive business practice.

VMD is not responsible or liable for such altered documentation. Resale of VMD's products with statements different from or beyond the parameters stated by VMD for that product or service voids all express or implied warranties for the associated VMD product or service and is an unfair and deceptive business practice.

All Rights Reserved.







## Via-Media Semiconductor Limited Company

<http://www.vmdsemi.com>

### Main Sites:

#### - Headquarters

Hangzhou Via-Media Semiconductor Co., LTD.  
1305-1306, Building 71, No. 90, Wensan Road, Xihu  
District, Hangzhou, Zhejiang Province, P.R. China  
Tel: +86-0571-8515 0563

#### - Chengdu Office

Chengdu Winhi Semiconductor Co., LTD.  
Floor 15, Building 5, No. 171, Hele 2<sup>nd</sup> Street,  
Chengdu, Sichuan Province, P.R. China  
Tel: +86-028-8505 0771

#### - Shanghai

Shanghai R&D Center.  
1506~1508, Xinyin Building, 888 Yishan Road,  
Shanghai, P.R of China  
Tel: +86- 021-54201999

#### - Shenzhen

Shenzhen Sales office  
Room 4A15, Block AB, Tianxiang Building,  
Chegongmiao , Futian District, Shenzhen, P.R of China  
Tel: +86-0755- 82570682

#### - Xi'an

Xi'an R&D Center  
1703B, Building A, Greenland Center, Jinye Road,  
High-Tech Zone, Xi'an, Shaanxi, P.R of China