



VMDSEMI

**VSTA065R44ANA**

**Datasheet**




VMDSEMI

## General Description

## Symbol

$V_{(BR)DSS}$	$R_{DS(ON)_{max}}$	$I_D$
650V	440mΩ@10V	10A




Symbol of VSTA065R44ANA

## Features

- $V_{DS} = 650V, I_D = 10A$
- $R_{DS(ON)_{max}} = 440mΩ @ V_{GS} = 10V$
- Extremely low switching loss
- Excellent stability and uniformity
- RoHS and Halogen-Free Compliant

## Package Type



Package Type of VSTA065R44ANA

## Application

- PC power
- LED lighting
- Telecom power
- Server power
- Solar/UPS

## Ordering Information

Product Name	Package	Marking
VSTA065R44ANA	TO-220	STA065R44ANA

## Absolute Maximum Ratings

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	$V_{DS}$	650	V
Gate-Source Voltage	$V_{GS}$	±30	V
Continuous Drain Current <sup>Note 1</sup> , $T_C=25^\circ\text{C}$	$I_D$	10	A
Pulsed Drain Current <sup>Note 2</sup> , $T_C=25^\circ\text{C}$	$I_{D, pulse}$	30	A
Continuous Diode Forward Current <sup>Note 1</sup> , $T_C=25^\circ\text{C}$	$I_S$	10	A
Diode Pulsed Current <sup>Note 2</sup> , $T_C=25^\circ\text{C}$	$I_{S, pulse}$	30	A
Max Power Dissipation <sup>Note 3</sup> , $T_C=25^\circ\text{C}$	$P_D$	110	W
Avalanche Current, Single Pulse <sup>Note 4</sup>	$I_{AS}$	4.5	A
Avalanche Energy, Single Pulse <sup>Note 4</sup>	$E_{AS}$	203	mJ
MOSFET dv/dt ruggedness, $V_{DS}=0\sim 480\text{V}$	dv/dt	50	V/ns
Reverse diode dv/dt, $V_{DS}=0\sim 480\text{V}$ , $I_{SD}\leq I_D$	dv/dt	15	V/ns
Operation and storage temperature	$T_J, T_{STG}$	-55 to 150	°C

## Thermal Resistance

Parameter	Symbol	Min	Typ	Max	Unit
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$		1.14		°C/W
Thermal Resistance, Junction-to-Ambient <sup>Note 5</sup>	$R_{\theta JA}$		62		

## Notes:

Note1: Calculated continuous current based on maximum allowable junction temperature.

Note2: Pulse width limited by safe operating area.







Note3: Based on max. junction temperature, using junction-case thermal resistance.







Note4:  $V_{DD}=50\text{V}$ ,  $V_{GS}=10\text{V}$ ,  $L=20\text{mH}$ , starting  $T_A=25^\circ\text{C}$ .


Note5: When mounted on 1 inch square copper board,  $t\leq 10\text{sec}$ . The value in any given application depends on the user's specific board design.

**Electrical Characteristics** ( $T_A = 25\text{ }^\circ\text{C}$ , unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
<b>Statistic Characteristics</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V, I_D=250\mu A$	650			V
Drain-Source Leakage Current	$I_{DSS}$	$V_{DS}=650V, V_{GS}=0V$			1	$\mu A$
Gate-Source Leakage Current	Forward	$I_{GSSF}, V_{GS}=30V, V_{DS}=0V$			100	nA
	Reverse	$I_{GSSR}, V_{GS}=-30V, V_{DS}=0V$			-100	
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	3.0		4.5	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	$V_{GS}=10V, I_D=5A$		385	440	$m\Omega$
Gate Resistance	$R_G$	$F=1MHz, \text{Open Drain}$		5.6		$\Omega$
<b>Dynamic Characteristics</b>						
Input Capacitance	$C_{iss}$	$V_{DS}=100V, V_{GS}=0V, f=1MHz$		691		pF
Output Capacitance	$C_{oss}$			73.9		pF
Reverse Transfer Capacitance	$C_{rss}$			1.9		pF
Turn-on Delay Time	$t_{d(on)}$	$V_{DS}=400V, I_D=5A, R_G=25\Omega, V_{GS}=10V$		17.8		ns
Rise Time	$t_r$			11.0		
Turn-off Delay Time	$t_{d(off)}$			53.2		
Fall Time	$t_f$			44.8		
<b>Gate Charge Characteristics</b>						
Gate to Source Charge	$Q_{gs}$	$V_{DS}=400V, I_D=5A, V_{GS}=0 \text{ to } 10V$		4.66		nC
Gate to Drain Charge	$Q_{gd}$			5.74		
Gate Charge Total	$Q_g$			16.11		
Gate Plateau Voltage	$V_{plateau}$			5.8		V
<b>Reverse Diode Characteristics</b>						
Drain-Source Diode Forward Voltage	$V_{SD}$	$V_{GS}=0V, I_S=1A$		0.75		V
Reverse Recovery Time	$t_{rr}$	$V_R=400V, I_S=5A, di/dt=100A/\mu s$		193		ns
Reverse Recovery Charge	$Q_{rr}$			1.79		$\mu C$
Peak Reverse Recovery Current	$I_{rrm}$			16.26		A

**Electrical Characteristics Diagrams**

**Figure 1. Typ. output characteristics**

**Figure 2. Typ. transfer characteristics**

**Figure 3. Typ. Capacitances**

**Figure 4. Typ. gate charge**

**Figure 5. Drain-source breakdown voltage**

**Figure 6. Drain-source on-state resistance**



**Figure 7. Threshold voltage**

**Figure 8. Forward characteristic of body diode**

**Figure 9. Drain-source on-state resistance**

**Figure 10. Drain current Derating**

**Figure 11. Power Dissipation**

**Figure 12. Safe operation area  $T_C = 25^\circ\text{C}$**



**Figure 13. Max. transient thermal impedance**

## Mechanical Dimensions

### TO-220 Package Information



# VMDSEMI



## NOTICE

Hangzhou VMD Semiconductor Co., Ltd (VMD) reserves the right to make changes without notice in order to improve reliability, function or design and to discontinue any product or service without notice. Customers should obtain the latest relevant information before orders and should verify that such information is current and complete. All products are sold subject to VMD's terms and conditions supplied at the time of order acknowledgement.

VMD, its affiliates, agents, and employees, and all persons acting on its or their behalf, disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

VMD disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify VMD's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

VMD warrants performance of its hardware products to the specifications at the time of sale, testing, reliability and quality control are used to the extent VMD deems necessary to support this warranty. Except where agreed upon by contractual agreement, testing of all parameters of each product is not necessarily performed.

VMD does not assume any liability arising from the use of any product or circuit designs described herein. Customers are responsible for their products and applications using VMD's components. To minimize risk, customers must provide adequate design and operating safeguards.

VMD does not warrant or convey any license to any intellectual property rights either expressed or implied under its patent rights, nor the rights of others. Reproduction of information in VMD's data sheets or data books is permissible only if reproduction is without modification or alteration. Reproduction of this information with any alteration is an unfair and deceptive business practice.

VMD is not responsible or liable for such altered documentation. Resale of VMD's products with statements different from or beyond the parameters stated by VMD for that product or service voids all express or implied warranties for the associated VMD product or service and is an unfair and deceptive business practice.

All Rights Reserved.





## Via-Media Semiconductor Limited Company

<http://www.vmdsemi.com>

### Main Sites:

#### - Headquarters

Hangzhou Via-Media Semiconductor Co., LTD.  
1305-1306, Building 71, No. 90, Wensan Road, Xihu  
District, Hangzhou, Zhejiang Province, P.R. China  
Tel: +86-0571-8515 0563

#### - Chengdu Office

Chengdu Winhi Semiconductor Co., LTD.  
Floor 15, Building 5, No. 171, Hele 2<sup>nd</sup> Street,  
Chengdu, Sichuan Province, P.R. China  
Tel: +86-028-8505 0771

#### - Shanghai

Shanghai R&D Center.  
1506~1508, Xinyin Building, 888 Yishan Road,  
Shanghai, P.R of China

Tel: +86-021-54201999

#### - Shenzhen

Shenzhen Sales office .  
Room 4A15, Block AB, Tianxiang Building,  
Chegongmiao, Futian District, Shenzhen, P.R of  
China

Tel: +86-0755-82570682

#### - Xi'an

Xi'an R&D Center  
1703B, Building A, Greenland Center, Jinye Road,  
High-Tech Zone, Xi'an, Shaanxi, P.R of China